

Heat pump model	Master Therm	BA22ISC-1
------------------------	---------------------	------------------

Heat pump type	Air/Water
Supplementary heater	Yes
Heat pump combination heater	Yes

Reference heating season		Average		
Reference water temperature		LOW, 35°C		
Full load heating	Prated [kW]	4.51		
Seasonal efficiency	η_s [%]	172		
Annual electricity consumption	Q_{HE} [kWh]	2128		
Average 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	3.99	2.74	0.900
B	2	2.58	4.16	0.900
C	7	1.64	6.22	0.900
D	12	2.08	7.50	0.938
TOL (E)	-10	3.64	2.61	0.900
Tbivalent (F)	-7	3.99	2.74	0.900

Reference heating season		Average		
Reference water temperature		High, 55°C		
Full load heating	Prated [kW]	4.44		
Seasonal efficiency	η_s [%]	130		
Annual electricity consumption	Q_{HE} [kWh]	2759		
Average 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	3.93	2.03	0.900
B	2	2.45	3.15	0.900
C	7	1.69	4.74	0.900
D	12	1.96	5.73	0.950
TOL (E)	-10	3.68	1.90	0.900
Tbivalent (F)	-7	3.93	2.03	0.900

Reference heating season		Warmer		
Reference water temperature		Low, 35°C		
Full load heating	Prated [kW]	5.32		
Seasonal efficiency	η_s [%]	239		
Annual electricity consumption	Q_{HE} [kWh]	1176		
Warmer 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
B	2	5.32	3.34	0.900
C	7	3.78	5.20	0.976
D	12	1.58	7.76	0.900
TOL (E)	2	5.32	3.34	0.900
Tbivalent (F)	2	5.32	3.34	0.900

Heat pump model	Master Therm	BA22ISC-1
------------------------	---------------------	------------------

Reference heating season		Warmer		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	5.08	
Seasonal efficiency		η_s [%]	164	
Annual electricity consumption		Q_{HE} [kWh]	1626	
Warmer 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
B	2	5.08	2.25	0.900
C	7	3.54	3.52	0.900
D	12	1.95	5.56	0.951
TOL (E)	2	5.08	2.25	0.900
Tbivalent (F)	2	5.08	2.25	0.900

Reference heating season		Colder		
Reference water temperature		Low, 35°C		
Full load heating		Prated [kW]	6.55	
Seasonal efficiency		η_s [%]	134	
Annual electricity consumption		Q_{HE} [kWh]	4717	
Colder 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	3.97	2.91	0.900
B	2	2.61	4.47	0.900
C	7	1.56	6.42	0.900
D	12	2.08	7.50	0.938
TOL (E)	-22	2.64	2.34	0.900
Tbivalent (F)	-7	3.97	2.91	0.900
G	-15	3.15	2.56	0.900

Reference heating season		Colder		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	6.49	
Seasonal efficiency		η_s [%]	110	
Annual electricity consumption		Q_{HE} [kWh]	5643	
Colder 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	3.93	2.33	0.900
B	2	2.50	3.53	0.900
C	7	1.73	5.18	0.948
D	12	1.99	6.12	0.947
TOL (E)	-22	2.84	1.88	0.900
Tbivalent (F)	-7	3.93	2.33	0.900
G	-15	3.26	2.05	0.900

Heat pump model	Master Therm	BA22ISC-1
------------------------	---------------------	------------------

Power consumption in modes other than "active mode"		
Off mode	P_{OFF} [kW]	0.018
Thermostat off mode	P_{TO} [kW]	0.017
Standby mode	P_{SB} [kW]	0.018
Crankcaseheater mode	P_{CK} [kW]	-

Supplementary heater capacity	P_{sup} [kW]	4.5
Supplementary heater type	[-]	electricity

Capacity control		Variable
Sound power level Indoor	L_{WA} [dBA]	48
Sound power level Outdoor	L_{WA} [dBA]	62
Rated airflow	[m ³ /h]	max.3000

Declared load profile / Tapping cycle		L
Daily electricity consumption	Q_{elec} [kWh]	3.129
Water heating energy efficiency	η_{wh} [%]	90

Temperature controller		
Type	Carel pCO5/pCO5+/uPC, Master Therm custom SW	
Class	II	
Contribution	%	2.0

Temperature controller + Room Terminal		
Type	Carel pCO5/pCO5+/uPC + pAD, Master Therm custom SW	
Class	VI	
Contribution	%	4.0

Heat pump model	Master Therm	BA22ISC-1
------------------------	---------------------	------------------

Information sheet			
Temperature application		Low, 35°C	High, 55°C
Space heating energy efficiency class, Average climate	-	A++	A++
Nominal heating capacity Pdesign, Average climate	kW	5	4
Space heating seasonal efficiency, Average climate	%	172	130
Space heating annual electricity consumption, Average cl.	kWh	2128	2759

Nominal heating capacity Pdesign, Colder climate	kW	7	6
Space heating seasonal efficiency, Colder climate	%	134	110
Space heating annual electricity consumption, Colder cl.	kWh	4717	5643

Nominal heating capacity Pdesign, Warmer climate	kW	5	5
Space heating seasonal efficiency, Warmer climate	%	239	164
Space heating annual electricity consumption, Warmer cl.	kWh	1176	1626

Sound power level Lwa Outdoor	dBA	62
-------------------------------	-----	----

Information sheet for energy efficiency Set with Temperature controller			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC, Class	-	II	II
Controller Carel pCO5/pCO5+/uPC, Contribution	%	2.0	2.0
Set Space heating seasonal efficiency, Average climate	%	174	132
Set Space heating energy efficiency class, Average climate	-	A++	A++
Set Space heating seasonal efficiency, Colder climate	%	136	112
Set Space heating seasonal efficiency, Warmer climate	%	241	166

Information sheet for energy efficiency Set with Temperature controller + Room Terminal			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC + pAD, Class	-	VI	VI
Controller Carel pCO5/pCO5+/uPC, +pAD, Contribution	%	4.0	4.0
Set Space heating seasonal efficiency, Average climate	%	176	134
Set Space heating energy efficiency class, Average climate	-	A+++	A++
Set Space heating seasonal efficiency, Colder climate	%	138	114
Set Space heating seasonal efficiency, Warmer climate	%	243	168

Heat pump model	Master Therm	BA26ISC-1
------------------------	---------------------	------------------

Heat pump type	Air/Water
Supplementary heater	Yes
Heat pump combination heater	Yes

Reference heating season		Average		
Reference water temperature		LOW, 35°C		
Full load heating	Prated [kW]	6.51		
Seasonal efficiency	η_s [%]	168	A++	
Annual electricity consumption		Q_{HE} [kWh]	3139	
Average 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T _j [°C]	P _{dh} [kW]	COP _d (-)	C _{dh} (-)
A	-7	5.76	2.59	0.900
B	2	3.72	3.91	0.900
C	7	2.42	6.53	0.900
D	12	2.74	7.21	0.951
TOL (E)	-10	5.88	2.52	0.900
Tbivalent (F)	-7	5.76	2.59	0.900

Reference heating season		Average		
Reference water temperature		High, 55°C		
Full load heating	Prated [kW]	6.33		
Seasonal efficiency	η_s [%]	126	A++	
Annual electricity consumption		Q_{HE} [kWh]	4039	
Average 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T _j [°C]	P _{dh} [kW]	COP _d (-)	C _{dh} (-)
A	-7	5.60	1.94	0.900
B	2	3.50	3.02	0.900
C	7	2.33	4.69	0.900
D	12	2.78	5.55	0.963
TOL (E)	-10	5.66	1.82	0.900
Tbivalent (F)	-7	5.60	1.94	0.900

Reference heating season		Warmer		
Reference water temperature		Low, 35°C		
Full load heating	Prated [kW]	7.67		
Seasonal efficiency	η_s [%]	259		
Annual electricity consumption		Q_{HE} [kWh]	1567	
Warmer 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T _j [°C]	P _{dh} [kW]	COP _d (-)	C _{dh} (-)
B	2	7.67	3.41	0.900
C	7	5.10	5.85	0.900
D	12	2.52	8.10	0.944
TOL (E)	2	7.67	3.41	0.900
Tbivalent (F)	2	7.67	3.41	0.900

Heat pump model	Master Therm	BA26ISC-1
------------------------	---------------------	------------------

Reference heating season		Warmer		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	7.40	
Seasonal efficiency		η_s [%]	177	
Annual electricity consumption		Q_{HE} [kWh]	2199	
Warmer 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
B	2	7.40	2.21	0.900
C	7	5.17	3.71	0.900
D	12	2.46	6.09	0.957
TOL (E)	2	7.40	2.21	0.900
Tbivalent (F)	2	7.40	2.21	0.900

Reference heating season		Colder		
Reference water temperature		Low, 35°C		
Full load heating		Prated [kW]	9.65	
Seasonal efficiency		η_s [%]	132	
Annual electricity consumption		Q_{HE} [kWh]	5987	
Colder 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	5.84	2.70	0.900
B	2	3.54	4.55	0.900
C	7	2.97	6.82	0.960
D	12	3.45	7.50	0.959
TOL (E)	-22	4.16	2.08	0.900
Tbivalent (F)	-7	5.84	2.70	0.900
G	-15	4.81	2.32	0.900

Reference heating season		Colder		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	9.31	
Seasonal efficiency		η_s [%]	107	
Annual electricity consumption		Q_{HE} [kWh]	7116	
Colder 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	5.63	2.17	0.900
B	2	3.69	3.58	0.900
C	7	2.86	5.58	0.966
D	12	3.33	6.22	0.965
TOL (E)	-22	3.53	1.42	0.900
Tbivalent (F)	-7	5.63	2.17	0.900
G	-15	4.34	1.71	0.900

Heat pump model	Master Therm	BA26ISC-1
------------------------	---------------------	------------------

Power consumption in modes other than "active mode"		
Off mode	P_{OFF} [kW]	0.018
Thermostat off mode	P_{TO} [kW]	0.017
Standby mode	P_{SB} [kW]	0.018
Crankcaseheater mode	P_{CK} [kW]	-

Supplementary heater capacity	P_{SUP} [kW]	6
Supplementary heater type	[-]	electricity

Capacity control		Variable
Sound power level Indoor	L_{WA} [dBA]	48
Sound power level Outdoor	L_{WA} [dBA]	62
Rated airflow	[m ³ /h]	max. 3500

Declared load profile / Tapping cycle		L
Daily electricity consumption	Q_{elec} [kWh]	3.129
Water heating energy efficiency	η_{wh} [%]	90

Temperature controller		
Type	Carel pCO5/pCO5+/uPC, Master Therm custom SW	
Class	II	
Contribution	%	2.0

Temperature controller + Room Terminal		
Type	Carel pCO5/pCO5+/uPC + pAD, Master Therm custom SW	
Class	VI	
Contribution	%	4.0

Heat pump model	Master Therm	BA26ISC-1
------------------------	---------------------	------------------

Information sheet			
Temperature application		Low, 35°C	High, 55°C
Space heating energy efficiency class, Average climate	-	A++	A++
Nominal heating capacity Pdesign, Average climate	kW	7	6
Space heating seasonal efficiency, Average climate	%	168	126
Space heating annual electricity consumption, Average cl.	kWh	3139	4039

Nominal heating capacity Pdesign, Colder climate	kW	10	9
Space heating seasonal efficiency, Colder climate	%	132	107
Space heating annual electricity consumption, Colder cl.	kWh	5987	7116

Nominal heating capacity Pdesign, Warmer climate	kW	8	7
Space heating seasonal efficiency, Warmer climate	%	259	177
Space heating annual electricity consumption, Warmer cl.	kWh	1567	2199

Sound power level Lwa Outdoor	dBA	62
-------------------------------	-----	----

Information sheet for energy efficiency Set with Temperature controller			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC, Class	-	II	II
Controller Carel pCO5/pCO5+/uPC, Contribution	%	2.0	2.0
Set Space heating seasonal efficiency, Average climate	%	170	128
Set Space heating energy efficiency class, Average climate	-	A++	A++
Set Space heating seasonal efficiency, Colder climate	%	134	109
Set Space heating seasonal efficiency, Warmer climate	%	261	179

Information sheet for energy efficiency Set with Temperature controller + Room Terminal			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC + pAD, Class	-	VI	VI
Controller Carel pCO5/pCO5+/uPC, +pAD, Contribution	%	4.0	4.0
Set Space heating seasonal efficiency, Average climate	%	172	130
Set Space heating energy efficiency class, Average climate	-	A++	A++
Set Space heating seasonal efficiency, Colder climate	%	136	111
Set Space heating seasonal efficiency, Warmer climate	%	263	181

Heat pump model	Master Therm	BA37ISC-1
------------------------	---------------------	------------------

Heat pump type	Air/Water
Supplementary heater	Yes
Heat pump combination heater	No

Reference heating season		Average		
Reference water temperature		LOW, 35°C		
Full load heating		Prated [kW]	10.93	
Seasonal efficiency		η_s [%]	176	A+++
Annual electricity consumption		Q_{HE} [kWh]	5035	
Average 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	9.67	2.64	0.900
B	2	6.10	4.38	0.900
C	7	4.06	6.19	0.900
D	12	4.75	7.62	0.961
TOL (E)	-10	9.04	2.48	0.900
Tbivalent (F)	-7	9.67	2.64	0.900

Reference heating season		Average		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	10.02	
Seasonal efficiency		η_s [%]	137	A++
Annual electricity consumption		Q_{HE} [kWh]	5910	
Average 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pdh [kW]	COPd (-)	Cdh (-)
A	-7	8.86	2.00	0.900
B	2	5.45	3.41	0.900
C	7	3.48	4.94	0.900
D	12	4.08	6.01	0.965
TOL (E)	-10	8.22	1.85	0.900
Tbivalent (F)	-7	8.86	2.00	0.900

Reference heating season		Warmer		
Reference water temperature		Low, 35°C		
Full load heating		Prated [kW]	12.45	
Seasonal efficiency		η_s [%]	249	
Annual electricity consumption		Q_{HE} [kWh]	2645	
Warmer 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pdh [kW]	COPd (-)	Cdh (-)
B	2	12.45	3.33	0.900
C	7	8.12	5.54	0.900
D	12	3.58	7.87	0.900
TOL (E)	-10	12.45	3.33	0.900
Tbivalent (F)	-7	12.45	3.33	0.900

Heat pump model	Master Therm	BA37ISC-1
------------------------	---------------------	------------------

Reference heating season		Warmer		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	11.14	
Seasonal efficiency		η_s [%]	175	
Annual electricity consumption		Q_{HE} [kWh]	3348	
Warmer 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
B	2	11.14	2.28	0.900
C	7	7.21	3.79	0.900
D	12	4.51	5.84	0.969
TOL (E)	-10	11.14	2.28	0.900
Tbivalent (F)	-7	11.14	2.28	0.900

Reference heating season		Colder		
Reference water temperature		Low, 35°C		
Full load heating		Prated [kW]	16.31	
Seasonal efficiency		η_s [%]	135	
Annual electricity consumption		Q_{HE} [kWh]	11678	
Colder 35°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	9.87	2.78	0.900
B	2	6.18	4.67	0.900
C	7	4.09	6.35	0.900
D	12	4.75	7.62	0.961
TOL (E)	-22	7.55	2.00	0.900
Tbivalent (F)	-7	9.87	2.78	0.900
G	-15	8.44	2.30	0.900

Reference heating season		Colder		
Reference water temperature		High, 55°C		
Full load heating		Prated [kW]	15.21	
Seasonal efficiency		η_s [%]	112	
Annual electricity consumption		Q_{HE} [kWh]	12984	
Colder 55°C	Outdoor heat exchanger	Declared capacity	COP at part load	Degradation Coefficient
	Outdoor air			
	T_j [°C]	Pd _h [kW]	COP _d (-)	Cdh (-)
A	-7	9.20	2.27	0.900
B	2	5.89	3.78	0.900
C	7	3.93	5.32	0.900
D	12	4.59	6.36	0.967
TOL (E)	-22	6.95	1.64	0.900
Tbivalent (F)	-7	9.20	2.27	0.900
G	-15	7.82	1.89	0.900

Heat pump model	Master Therm	BA37ISC-1
------------------------	---------------------	------------------

Power consumption in modes other than "active mode"		
Off mode	P_{OFF} [kW]	0.026
Thermostat off mode	P_{TO} [kW]	0.024
Standby mode	P_{SB} [kW]	0.026
Crankcaseheater mode	P_{CK} [kW]	-

Supplementary heater capacity	P_{sup} [kW]	6.0
Supplementary heater type	[-]	electricity

Capacity control		Variable
Sound power level Indoor	L_{WA} [dBA]	48
Sound power level Outdoor	L_{WA} [dBA]	62
Rated airflow	[m ³ /h]	max.6000

Declared load profile / Tapping cycle		L
Daily electricity consumption	Q_{elec} [kWh]	3.129
Water heating energy efficiency	η_{wh} [%]	90

Temperature controller		
Type	Carel pCO5/pCO5+/uPC, Master Therm custom SW	
Class	II	
Contribution	%	2.0

Temperature controller + Room Terminal		
Type	Carel pCO5/pCO5+/uPC + pAD, Master Therm custom SW	
Class	VI	
Contribution	%	4.0

Heat pump model	Master Therm	BA37ISC-1
------------------------	---------------------	------------------

Information sheet			
Temperature application		Low, 35°C	High, 55°C
Space heating energy efficiency class, Average climate	-	A+++	A++
Nominal heating capacity Pdesign, Average climate	kW	11	10
Space heating seasonal efficiency, Average climate	%	176	137
Space heating annual electricity consumption, Average cl.	kWh	5035	5910

Nominal heating capacity Pdesign, Colder climate	kW	16	15
Space heating seasonal efficiency, Colder climate	%	135	112
Space heating annual electricity consumption, Colder cl.	kWh	11678	12984

Nominal heating capacity Pdesign, Warmer climate	kW	12	11
Space heating seasonal efficiency, Warmer climate	%	249	175
Space heating annual electricity consumption, Warmer cl.	kWh	2645	3348

Sound power level Lwa Outdoor	dBA	62	
-------------------------------	-----	----	--

Information sheet for energy efficiency Set with Temperature controller			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC, Class	-	II	II
Controller Carel pCO5/pCO5+/uPC, Contribution	%	2.0	2.0
Set Space heating seasonal efficiency, Average climate	%	178	139
Set Space heating energy efficiency class, Average climate	-	A+++	A++
Set Space heating seasonal efficiency, Colder climate	%	137	114
Set Space heating seasonal efficiency, Warmer climate	%	251	177

Information sheet for energy efficiency Set with Temperature controller + Room Terminal			
Temperature application		Low, 35°C	High, 55°C
Controller Carel pCO5/pCO5+/uPC + pAD, Class	-	VI	VI
Controller Carel pCO5/pCO5+/uPC, +pAD, Contribution	%	4.0	4.0
Set Space heating seasonal efficiency, Average climate	%	180	141
Set Space heating energy efficiency class, Average climate	-	A+++	A++
Set Space heating seasonal efficiency, Colder climate	%	139	116
Set Space heating seasonal efficiency, Warmer climate	%	253	179